

noxmedical.com

nox MEDICAL

Nox Product Catalog

LBL-0171-REV13



Contact

Nox Medical

13B-1010 Polytek St.

Ottawa, ON K1J 9H9

Canada

Tel: +1(249) 50SLEEP

+1 (249) 507-5337

sales@noxmedical.com

www.noxmedical.com

Nox Medical is a leading provider in the field of sleep diagnostic solutions that build on decades of experience in providing industry standard solutions for sleep monitoring and diagnostics as well as bleeding edge technology. Our main goal is to bring to market a new generation of products to support the growth of sleep medicine.

Nox A1s™ and Nox T3s™, our flagship products are revolutionary sleep monitors, based on the latest innovations in wireless, memory, sensors, and electronic technology. These recording devices are compact, lightweight and easy to use.

Nox Recording Devices have been engineered and designed to record and analyze sleep disorders in children as well as adults. With the monitors we have managed to remove as many sensor leads as possible since the patient's comfort is the key element for good sleep recording.

Combining **Nox Recording Devices** with the powerful Noxturnal software unleashes the full potential of the Nox systems. Offering automatic analysis, scoring and reporting, Noxturnal greatly simplifies the task of preparing a sleep study for the correct interpretation by the physicians.

Nox Medical will always aim to proactively satisfy its customers' needs. The customer service representatives are trained to handle customer requests promptly and professionally. Personalized customer service, along with prompt delivery, are major priorities in keeping commitments to customers.


Contents

NOX SYSTEMS	3
Nox T3s™ System with WristOx2™, CE	3
Nox A1s™ System with WristOx2™, CE	4
SOFTWARE & LICENSES	5
Nox C1 DC Channel License	5
Noxturnal EDF File Format License	5
SYSTEM EXTENSIONS	5
Nox C1s Kit	5
Bluetooth™ 5.0 dongle	6
WristOx2™ Kit, Model 3150 BLE	6
Nox SAS SOLUTION	7
Nox SAS Consumables	8
CONSUMABLES	9
Nox RIP Belts	9
Cannulas	9
Airflow Sensors	10
Oximeter Sensors	12
Leads and Electrodes	14
Gels & Pastes	17
SYSTEM COMPONENTS	18

NOX SYSTEMS

Ref No	Unit pr Pack	Description
51 10 12	1	Nox T3s™ system with WristOx2™, CE
		<p>The Nox T3s™ System is a high-end respiratory sleep diagnostic system. It comes with the Noxturnal analysis software. The Nox T3s™ is designed for both adult and pediatric patients.</p>  <p>The Nox T3s™ system includes:</p>
56 10 11		Nox T3s™ recorder*, CE
56 12 12		Nox abdomen cable, s version
55 10 30		Nox RIP belts disposable, medium – 2 sets
55 20 10		Nox cannula with filter – 2 units
56 20 16		USB-C cable
56 80 12		Nox carry case, s version
56 90 14		Nox lid key
54 10 12		Nonin WristOx2™ kit, model 3150 BLE® pack*, includes:
55 30 20		WristOx2™ soft sensor, medium size
56 40 42		WristOx2™ model 3150 wristband
91 00 08		CD-ROM of the operators manual
53 90 10		Noxturnal CD
N/A		Nox T3s™ system leaflet
N/A		AA battery – 2 units
N/A		AAA battery – 2 units

*Warranty covered for 2 years (applies only to the main hardware units, marked with an *)*

Ref No	Unit pr Pack	Description
51 30 12	1	Nox A1s™ system with WristOx2™, CE
<p>The Nox A1s™ System is an ambulatory, polysomnography system, fully compliant to the AASM standards.</p> <p>The Nox A1s™ opens a new era in sleep diagnostic, designed with flexibility, study integrity and patient comfort in mind.</p> <p>The Nox A1s™ system includes:</p>		
		
56 14 11		Nox A1s™ recorder*, CE
56 21 10		Nox A1s™ EEG head cable 90 cm (35 in), adult
55 44 11		Nox A1s™ EEG 5 lead gold electrode cable - 2 pieces
56 12 12		Nox abdomen cable, s version
95 10 X2		Nox RIP belts, disposable (sizes medium and large - 1 pair of each)
55 20 10		Nox cannula with filter – 2 units
55 43 10		Nox snap-on double lead, orange 50/100cm (20/40 inch)
55 43 12		Nox snap-on double lead, gray 148/150cm (58/60 inch)
55 43 14		Nox snap-on double lead, black 148/150cm (58/60 inch)
56 20 16		USB-C cable
56 80 12		Nox carry case, s version
56 90 14		Nox lid key
54 10 12		Nonin WristOx2™ kit, model 3150 BLE® pack*, includes
55 30 20		WristOx2™ soft sensor, medium size
56 40 42		WristOx2™ 3150 wristband
91 00 08		CD-ROM of the operators manual
53 90 10		Noxturnal CD
N/A		Nox A1s™ system leaflet
N/A		Noxturnal App insert
N/A		AA lithium battery – 2 units
N/A		AAA battery – 2 units


*Warranty covered for 2 years (applies only to the main hardware unit, marked with an *)*

SOFTWARE & LICENSES

Ref No	Unit pr Pack	Description
53 60 13	1	Nox C1 DC channel license
<p>This license enables the DC channels on the Nox C1 Access Point. They will allow you to connect other auxiliary devices that have DC output to the Nox C1 Access Point.</p>		

Ref No	Unit pr Pack	Description
53 61 11	1	Noxturnal EDF file format license
<p>This license enables Noxturnal to read and review recordings in the EDF file format.</p>		

SYSTEM EXTENSIONS

Ref No	Unit pr Pack	Description
54 40 23	1	Nox C1s kit
<p>The Nox C1 Access Point is a wireless access point that together with the Bluetooth™5.0 dongle enables measurement, receiving and streaming of physiological signals during sleep. The Nox C1 is intended to be used with the Nox A1s™ system to enable online functionality of the system and allow for up to 12 auxiliary DC input channels.</p> <p>Includes:</p> <ul style="list-style-type: none"> • Nox C1 Access Point • Nox C1 power supply, incl. EU/JP/US/UK plugs • Nox C1 manual • Bluetooth™ 5.0 dongle 		
		

Warranty covered for 2 years (applies only to the main hardware unit)

Ref No	Unit pr Pack	Description
54 40 30	1	Bluetooth™ 5.0 dongle
<p>The Bluetooth™ 5.0 dongle is an essential extension to the Nox C1 Access Point enabling Bluetooth™ 5.0 connection with the Nox A1s™. The Bluetooth™ 5.0 dongle is plugged into one of the two USB ports of the Nox C1.</p>		



Ref No	Unit pr Pack	Description
54 10 12	1	WristOx2™ kit, model 3150 BLE
<p>Engineered with Nonin Medical's proven PureSAT SPO2 technology and updated with additional performance and reporting features, the WristOx2™ model 3150 is the most advanced wrist-worn pulse oximeter available. The Nonin 3150 BLE is an integrated part of the Nox sleep recording devices and provides pulse rate and blood oxygen saturation signals.</p> <p>Includes:</p> <ul style="list-style-type: none"> • WristOx2™ soft sensor, medium size • WristOx2™ 3150 wristband • CD-ROM of the operators manual 		



Warranty covered for 2 years

Nox SAS SOLUTION

Ref No	Unit pr Pack	Description
56 22 15	1	Nox SAS Head Cable, CE

Specifications:

- The Nox SAS Solution features a new, flexible way to record EEG data during polysomnography sleep studies conducted with the Nox A1s PSG system
- The patient side has two cables extending from the proxy connector
 - First cable is terminated with two USB-Micro structured connectors intended to be mated with Nox SAS Body Cables (left and right)
 - Second connected cable is terminated with 5 pair of double snap-on sockets that are intended to be connected to five Nox Double Snap Electrodes to record EEG, EOG and EMG
- The proxy connector connects to the unipolar and bipolar channels on the Nox A1s recording device
- Reusable




Warranty covered for 6 months

Ref No	Unit pr Pack	Description
56 22 14	1	Nox SAS Body Cable, CE (Left)
56 22 13	1	Nox SAS Body Cable, CE (Right)

Specifications:

- The Nox SAS Body Cable provides a single cable to record ECG and limb EMG with the Nox SAS Solution
- The Nox SAS Body Cable comes in two different colors to aid in easier set-up
 - Right - Blue
 - Left - Red
- Reusable



Warranty covered for 6 months

Nox SAS CONSUMABLES

Ref No	Sets pr Pack	Description
55 90 43	20	Nox SAS Electrode Pack (20 kits)
<p>Specifications:</p> <ul style="list-style-type: none"> One Nox SAS Electrode Pack includes <ul style="list-style-type: none"> 5x Single snap Nox SAS electrodes 8x Double snap Nox SAS electrodes 6x long Nox adhesive strips 4x short Nox adhesive strips The Nox Electrodes are single-use snap-on cutaneous electrodes that are applied directly onto the patient's skin. The Nox adhesive strips are intended to secure the electrode cables that attach to the Nox SAS electrodes to minimize the odds of the electrodes falling off the subject 		




Not warranty covered

Ref No	Unit pr Pack	Description
55 90 31	20	Nox SAS neck band (pack of 20)
<p>Specifications:</p> <ul style="list-style-type: none"> The Nox SAS neck band is used to attach the disposable carton to the patient's neck for further convenience when conducting the hook-up. The SAS Neck Band is an elastic tubular banded material, made out of bamboo. 		



Not warranty covered

Ref No	Unit pr Pack	Description
55 90 44	20	Nox SAS Disposable Carton (pack of 20)
<p>Specifications:</p> <ul style="list-style-type: none"> The Nox SAS disposable carton is used to align the components in the package for convenience. The carton is made from paper and is applied on the patient's thorax over clothing during the hook-up. The carton is disposable 		



Not warranty covered

CONSUMABLES

Nox RIP Belts

Ref No	Sets pr Pack	Description
55 10 10	20	Nox RIP belts disposable, pediatric
55 10 20	20	Nox RIP belts disposable, small
55 10 30	20	Nox RIP belts disposable, medium
55 10 40	20	Nox RIP belts disposable, large
55 10 50	14	Nox RIP belts disposable, extra large

Specifications:

- Nox RIP belts are very accurate in determining the effort of breathing
- To be used with both Nox A1s™ and Nox T3s™ systems
- High quality signals
- Super stretchable and elastic
- Comfortable for patient and easy to install
- Easy to adjust
- Single use/disposable



Not warranty covered

Cannulas


Ref No	Unit pr Pack	Description
55 20 10	40	Nox cannula with filter, adult

Specifications:


- The filter fits directly into the pressure connector on Nox recording devices. Can be used with the Nox A1s™ and Nox T3s™ (classic version or s version)
- Total length is 90cm/35in
- Airflow pressure
- Single use/disposable



Not warranty covered


Ref No	Unit pr Pack	Description
55 21 51	25	Cannula with luer-lock, pediatric
Specifications <ul style="list-style-type: none"> • Male luer connector • Total length is 210cm/84in • Gas sampling line • Airflow pressure • Single use/disposable 		

Not warranty covered


Ref No	Unit pr Pack	Description
55 21 10	50	Nox filter tube connectors
Connector between the Nox A1s™ or Nox T3s™ recording device and the Nox cannula with luer-lock or mask tubing.		

Not warranty covered


Airflow Sensors

Ref No	Unit pr Pack	Description
55 22 30	1	Thermal flow sensor, reusable (adult)
Specifications: <ul style="list-style-type: none"> • Bipolar Touch-Proof keyhole connector • Thermistor flow sensor • Comfortable, adjustable and easy patient application 		


Warranty covered for 6 months

Ref No	Unit pr Pack	Description
55 28 10	1	Pneumo flow sensor
The pneumo flow sensor can be used to connect flow generator and the differential pressure port on the Nox C1 Access Point (REF 54 40 23).		


Not warranty covered

Ref No	Unit pr Pack	Description
55 28 11	1	Pneumo flow straight adapter
Specifications: <ul style="list-style-type: none"> • Replacement adapter for the pneumo flow sensor • Connects to the flow generator • Size 15mm ID x 22mm ID 		

Not warranty covered

Ref No	Unit pr Pack	Description
55 28 12	1	Pneumo flow straight connector
Specifications: <ul style="list-style-type: none"> • Replacement connector for the pneumo flow sensor • Connects to the mask tube • Size 22mm OD x 22mm ID x 15mm ID 		

Not warranty covered

Ref No	Unit pr Pack	Description
55 21 15	50	PT1 hydrophobic filters
Specification: <ul style="list-style-type: none"> • Two filters are attached to the two tubes located on the pneumo flow sensor (Ref 55 28 10) • Connects to the input of the pressure transducer sensor • Single use 		


Not warranty covered

Oximeter Sensors

Ref No	Unit pr Pack	Description
55 30 10	1	WristOx2™ soft sensor, small
55 30 20	1	WristOx2™ soft sensor, medium
55 30 30	1	WristOx2™ soft sensor, large

Specifications:

- Preferred application on the fingers or toes
- Reusable




Warranty covered for 2 years

Ref No	Unit pr Pack	Description
55 31 20	1	Flex Sensor with FlexiWraps, infant

Specifications:

- Patient Range 2-20kg (4-44 lbs)
- Preferred application: toe, thumb, medial aspect of hand
- 1 meter cable
- Reusable, made of durable silicone
- Packed with 25 disposable FlexiWraps for infants

Note: The Flex Sensors 3150I sensor adapter cable is needed, Ref No 55 39 10.




Warranty covered for 3 months

Ref No	Unit pr Pack	Description
55 31 30	1	WristOx2™ Flex Sensor with FlexiWraps, adult


Specifications:

- Patient Range > 20kg (> 44lbs)
- Preferred application: index, middle or ring fingers
- Reusable, made of durable silicone
- 30cm cable
- Ideal for numerous applications, including extended monitoring and sleep studies
- Packed with 25 disposable FlexiWraps for adults



Warranty covered for 3 months

Ref No	Unit pr Pack	Description
55 31 21	25	FlexiWraps, infant
55 31 31	25	FlexiWraps, adult
<p>Specifications:</p> <ul style="list-style-type: none"> • FlexiWraps to use with Nonin's Flex Sensors • Single use/disposable 		




Not warranty covered

Ref No	Unit pr Pack	Description
55 39 10	1	WristOx2™ 3150 sensor adapter cable
<p>All Nonin sensors that are not WristOx2™ sensors can be used with the WristOx2™ model 3150 with this adapter cable.</p>		




Warranty covered for 6 months

Leads and Electrodes

Ref No	Unit pr Pack	Description
55 44 11	1	Nox A1™ EEG 5 lead gold electrode cable
<p>Specifications:</p> <ul style="list-style-type: none"> • Five different colored EEG leads with gold plated cup electrodes • The colors of the leads are: <ul style="list-style-type: none"> • Green (EOG) • Blue (F3/F4) • Yellow (C3/C4) • Grey (O1/O2) • Red (A1/A2) • The gold cup electrodes are intended to enable recording of EEG/EOG signals during sleep studies • 10mm diameter gold plated electrode • The electrodes are intended for both pediatric and adult patients • Reusable 		
		

Warranty covered for 6 months

Ref No	Unit pr Pack	Description
55 42 20	10	Neuroline cup disposable EEG electrodes
<p>Specifications:</p> <ul style="list-style-type: none"> • 100 cm • Female 1.5mm safety connector • Advanced silver/silver chloride sensor ensures uniform high signal quality • Pre-attached tangle-free lead wires • Color coded lead wires for easy handling • No risk of cross-contamination 		
		

Not warranty covered

Ref No	Unit pr Pack	Description
		Nox snap-on lead:
55 40 20	2	<ul style="list-style-type: none"> • 50 cm (20 inch), white
55 40 21	2	<ul style="list-style-type: none"> • 30 cm (12 inch), beige-white
55 40 22	1	<ul style="list-style-type: none"> • 100 cm (40 inch), green
55 40 23	1	<ul style="list-style-type: none"> • 50 cm (20 inch), beige-green
55 40 24	2	<ul style="list-style-type: none"> • 150 cm (60 inch), gray

55 40 25	2	<ul style="list-style-type: none"> • 100 cm (40 inch), beige-gray
55 40 26	2	<ul style="list-style-type: none"> • 150 cm (60 inch), black
55 40 27	2	<ul style="list-style-type: none"> • 100 cm (40 inch), beige-black
55 40 28	2	<ul style="list-style-type: none"> • 100 cm (40 inch), orange

Specifications:

- Electrode cable with female 1.5mm Touch-Proof safety connector and snap-on head
- For use with button snap type electrodes
- White colored leads are in ideal lengths for bruxism recordings
- Green colored leads are ideal for the patient ground
- Gray and black colored leads are ideal for LM recordings
- Orange colored leads are ideal for ECG recordings
- The leads with beige colored heads are ideal for pediatrics
- Reusable



Warranty covered for 3 months

Ref No	Unit pr Pack	Description
		Nox snap-on double lead:
55 43 10	1	<ul style="list-style-type: none"> • 50/100 cm (20/40 inch), orange
55 43 11	1	<ul style="list-style-type: none"> • 30/50 cm (12/20 inch), beige-orange
55 43 12	1	<ul style="list-style-type: none"> • 148/150 cm (58/60 inch), gray
55 43 13	1	<ul style="list-style-type: none"> • 98/100 cm (39/40 inch), beige-gray
55 43 14	1	<ul style="list-style-type: none"> • 148/150 cm (58/60 inch), black
55 43 15	1	<ul style="list-style-type: none"> • 98/100 cm (39/40 inch), beige-black
55 43 16	1	<ul style="list-style-type: none"> • 50/52 cm (20/21 inch), white
55 43 17	1	<ul style="list-style-type: none"> • 30/32 cm (12/13 inch), beige-white

Specifications:

- Bipolar keyhole connector on one end and snap-on heads on the other
- For use with button snap type electrodes
- Electrode cable is divided into two separated leads with snap-on heads
- Orange colored cables are ideal for ECG recordings
- Grey and black colored cables are ideal for LM recordings
- White colored cables are ideal for bruxism recordings
- The leads with beige colored heads are ideal for pediatrics
- Reusable



Warranty covered for 3 months

Ref No	Unit pr Pack	Description
55 41 11	12	Lead with attached electrode, 50 cm (20 inch)

Specifications:

- Ideal for EMG recordings
- Skin contact size 28 x 20mm electrode with solid gel
- The small size makes it easy to use on the facial area and pediatrics
- Transparent backing allows precise placement of sensor
- High quality Ag/AgCl sensor for optimal signal quality
- Female 1.5mm safety connector
- Wound lead wires for easier handling
- Each bag contains 4 x 3 electrodes on plastic film
- Single use/disposable



Not warranty covered

Ref No	Unit pr Pack	Description
55 42 09	25	Blue Sensor™ N electrode (small)

Specifications:

- The small size makes it easy to use in the facial area and on pediatrics
- 3.0 x 2.2 cm (1.18 x 0.90 inch) snap-on electrode with gel
- Silver/silver chloride sensor
- Adhesion ensures that the electrode stays in place
- Single use/disposable



Not warranty covered

Ref No	Unit pr Pack	Description
55 42 10	50	Blue Sensor™ M electrode

Specifications:

- Ideal for EMG or ECG recordings
- 3.4 cm (1.25 inch) snap-on electrode with gel
- Silver/silver chloride sensor
- Adhesion ensures that the electrode stays in place
- Single use/disposable



Not warranty covered

Gels & Pastes

Ref No	Unit pr Pack	Description
55 50 10	3	Nuprep skin prep gel
<p>Specifications:</p> <ul style="list-style-type: none"> • A mild abrasive prepping gel to reduce skin impedance • Maximum efficiency on test results • 114 gr (4 oz) tube. EEG, EMG, and ECG prepping gel • Sold in pack of 3 tubes 		



Not warranty covered

Ref No	Unit pr Pack	Description
55 50 20	3	Ten20 conductive EEG paste
<p>Specifications:</p> <ul style="list-style-type: none"> • Adhesive paste which holds electrodes in place while allowing the transmittance of electrical signals • Washable and non-drying • 114 gr (4 oz) jars • Sold in packs of 3 jars 		




Not warranty covered

Ref No	Unit pr Pack	Description
55 50 31	12	Tensive conductive adhesive gel
<p>Specifications:</p> <ul style="list-style-type: none"> • Provides a durable, cohesive and adherent combination needed for accurate recording • Water soluble • 50 gr per tube • Sold in packs of 12 tubes 		




Not warranty covered

SYSTEM COMPONENTS

Ref No	Unit pr Pack	Description
56 20 10	1	Nox abdomen cable
Connects the abdomen RIP belt to the Nox A1™ and Nox T3™ recording devices.		

Warranty covered for 6 months

Ref No	Unit pr Pack	Description
56 12 12	1	Nox abdomen cable, s
Connects the abdomen RIP belt to the Nox A1™ and Nox T3™ recording devices (s version).		

Warranty covered for 6 months

Ref No	Unit pr Pack	Description
56 20 12	1	Analog DC extension cable (Nox C1)
Allows users to extend the analog inputs by 1.5 m to facilitate connections to 3 rd party sensors and devices.		

Warranty covered for 12 months

Ref No	Unit pr Pack	Description
56 20 13	1	Serial cable (Nox C1)
Allows users to connect serial outputs to the serial ports on the back of the Nox C1 Access Point. The package also contains a null modem and a gender changer for the possibility to connect any DB9 serial connector. The package contains 3.5 mm male to DB9 female serial cable (2 m), null nodem and a gender changer.		

Warranty covered for 12 months

Ref No	Unit pr Pack	Description
56 20 14	1	Analog DC splitter cable (Nox C1)
Plugs into the DC analog inputs on the Nox C1 to enable individual access to each channel of the stereo analog inputs on the front of the Nox C1.		

Warranty covered for 12 months

Ref No	Unit pr Pack	Description
56 21 10	1	Nox A1™ EEG head cable, adult (90 cm/35 inch)
56 21 11	1	Nox A1™ EEG head cable, pediatric (70 cm/28 inch)
<p>Specifications:</p> <ul style="list-style-type: none"> • One end is snapped on a ground electrode fastened on the patient's forehead • Other end is 10 unipolar EEG channels and one ground channel that connects to the Nox A1s™ • Two Nox A1s™ EEG 5 lead gold electrode cables connect to the cable via mini USB 		



Warranty covered for 6 months

Ref No	Unit pr Pack	Description
56 90 11	1	Nox battery lid (T3™/A1™)
<p>Replacement battery lid for the Nox A1™ and the Nox T3™ recording devices</p>		



Not warranty covered

Ref No	Unit pr Pack	Description
56 90 20	1	Nox battery lid, s
<p>Replacement battery lid for the Nox A1s™ and the Nox T3s™ recording devices (s version)</p>		




Not warranty covered


Ref No	Unit pr Pack	Description
56 90 13	2	Nox clip strap, 2 pcs
<p>Replacement clips for the Nox T3™ and Nox A1™ recording devices</p>		



Not warranty covered

Ref No	Unit pr Pack	Description
56 90 21	2	Nox clip straps, s
Replacement clips for the Nox T3s™ and Nox A1s™ recording devices (s version)		

Not warranty covered

Ref No	Unit pr Pack	Description
56 90 18	1	WristOx2™ 3150 battery lid
Replacement battery lid for the Nonin WristOx2™, model 3150		


Not warranty covered

Ref No	Unit pr Pack	Description
56 40 43	1	WristOx2™ 3150 Battery Spring
Replacement battery spring for the Nonin WristOx2™ model 3150.		


Not warranty covered

Ref No	Unit pr Pack	Description
56 28 13	1	Keyhole 2 x 1.5mm safety connector male
Specifications:		
<ul style="list-style-type: none"> Used to connect products with bipolar 1.5mm female safety connectors to the Nox T3s™ and the Nox A1s™ recording devices 		


Warranty Covered for 6 months

Ref No	Unit pr Pack	Description
56 80 11	1	Nox A1™ carry case
Replacement carry case for the Nox A1™ system		


Not warranty covered

Ref No	Unit pr Pack	Description
56 80 12	1	Nox carry case, s
Replacement carry case for the Nox T3s™ and the Nox A1s™ (s version)		

Not warranty covered

Ref No	Unit pr Pack	Description
56 90 14	1	Nox lid key
Key to open the Nox device's battery lid. (All recording devices)		


Not warranty covered

Ref No	Unit pr Pack	Description
56 20 11	1	Nox mini USB cable
Used to connect the Nox recording devices to a computer. With standard USB on one end and mini USB on the other end.		

Not warranty covered

Ref No	Unit pr Pack	Description
56 20 16	1	USB-C cable
Used to connect the Nox T3s™ and Nox A1s™ recording device to a computer. With standard USB on one end and USB-C on the other end.		


Not warranty covered

Ref No	Unit pr Pack	Description
56 40 42	1	WristOx2™ 3150 wristband
Specifications: <ul style="list-style-type: none"> • Wristband for the Nonin 3150 wrist pulse oximeter • Comfortable for patient • Easy to adjust 		


Not warranty covered

Ref No	Unit pr Pack	Description
56 40 50	250	VERI-COLOR Big Band 140 wristband
<p>Specifications:</p> <ul style="list-style-type: none"> • Single use wristband for the Nonin 3150 wrist pulse oximeter • Attaches the oximeter to patient for chain of custody • Easy to adjust 		

Not warranty covered

Ref No	Unit pr Pack	Description
56 30 91	4	MAHA Powerex rechargeable 2700mAh batteries
<p>Specifications:</p> <ul style="list-style-type: none"> • High quality rechargeable batteries • Nickel-metal hydride (NiMH) chemistry • 4 batteries to a pack • 1.2V charge and 2700mAh capacity • Use with 56 30 92 battery charger MAHA 		

Not warranty covered

Ref No	Unit pr Pack	Description
56 30 96	1	MAHA Powerex battery charger MH-C980
<p>Specifications:</p> <ul style="list-style-type: none"> • The battery charger recommended by Nox Medical • Eight Cell 1-Hr PRO AA/AAA charger with turbo charge mode • LCD display • Thermal management system • US plug 		

Warranty covered for 2 years

Ref No		
54 80 18	1	IP camera
<p>Specifications:</p> <ul style="list-style-type: none"> • Axis IP dome camera, model P3265-LV • Multifocal lens, digital PTZ function • PoE power supply, automatic LAN detection • Supports HTTP, RTSP, TCP/IP and other protocols • Night vision, infrared with distance of 40 meters, color video input available, motion detection, 2.6 optical zoom • 8 GB flash memory, 1 GB RAM, microSD card • Maximum digital video resolution of 1920 x 1080 (60 fps) • Two-way audio support • Height 4.1 inches x width 5.9 inches and weights 22.93 ounces 		



Inquire for warranty coverage

Ref No		
54 80 22	1	Network PoE switch
<p>Specifications:</p> <ul style="list-style-type: none"> • Netgear 8-Port GB PoE unmanaged switch • Allows users to connect and power PoE devices such as wireless access points and/or IP cameras • 8 PoE inputs 		



Not warranty covered

Ref No		
54 80 23	1	USB to Ethernet adapter
<p>Specifications:</p> <ul style="list-style-type: none"> • TRENDnet Gigabit Ethernet Network Adapter - USB 3.0 • Model TU3-ETG • RJ-45 1000BASE-T port • Maximum speed of 1 GBit/sec • Featuring a USB-A interface 		



Not warranty covered

All information contained in this catalog is subject to change without notice.

Nox Medical is not responsible for any loss which results from any error in the product code or identification contained herein.

If you have any comments about our products and accessories, please help us to make our products even better by calling us or sending an e-mail: support@noxmedical.com.